# ECHO VOYAGER

# Extra Large Unmanned Undersea Vehicle

#### **Current Environment**

Unmanned Undersea Vehicles (UUVs), due to their limited endurance, require host platforms for launch and recovery. That reliance results in signi cant size restrictions limiting on-board power availability, precluding incorporation of redundancy for long-term operations, and reducing payload capacity. At the same time, new sensor and system payloads are rapidly being introduced that could expand the UUV mission set. Viable, costeffective UUVs providing endurance capabilities and meeting modular payload requirements for varied missions are needed to support the demonstration and re nement of capabilities in open ocean environments.

Boeing's Echo Voyager, a multi-market, pier-launched, modular, long-range Extra Large Unmanned Undersea Vehicle (XLUUV) shifts that paradigm.



#### **The Boeing Solution**

Echo Voyager is a game-changing platform, capable of performing as a multi-mission system and playing a pivotal role in future force structure. The vehicle's advanced autonomy allows it to operate for months at a time without physical human contact and in congested waters. Echo Voyager is complete with a generous internal and external payload volume and available energy capacity. Echo Voyager is the next generation of UUVs.

- Host Ship Independent
- Swims from port
- 6,500 nm range (1 fuel module)
- Fully autonomous

#### **Navigation System**

The vehicle provides remarkable navigational accuracy. The primary navigation system features a proven Kalman Itered Inertial Navigation Unit (INU) aided by a set of Doppler Velocity Logs (DVLs), and depth sensors, and can use sea oor long baseline (LBL) transponders to augment the navigation solution. GPS is available operating on or near the surface.

The Boeing Company Advanced Technology Programs 5301 Bolsa Avenue M/C H038-B003 Huntington Beach, CA 92647

Key navigation performance characteristics:

- Altitude Stability: 0.8 ft / 0.25 m ‡
- Depth Stability: 1.0 ft / 0.3 m ‡
- LBL aided position accuracy: 7.7 ft / 2.3 m ‡
- Unaided position accuracy: 0.15% distance traveled ±: RMS values

#### Communications

The vehicle uses encrypted Inmarsat IV, Iridium, Wi-Fi, and/or freewave enabled communications for operational command. control, system status, and mission re-planning during nearsurface operations, and acoustic communications for command, control, and status messages during submerged operations.

## **Buoyancy Control and Trim**

The vehicle features an active buoyancy control system with the A fully autonomous vehicle featuring: following features:

- Autonomous buoyancy control capability
- Forward and aft trim control
- Sea oor mooring capability

#### **Obstacle Avoidance**

The vehicle features an active obstacle avoidance capability. The capability is enabled by a Forward-Looking Sonar (FLS) and proven autonomous obstacle avoidance algorithms.

### Terrain Following

The vehicle's FLS system along with a DVL enable terrain following mission capability operations near the sea oor.

# Modular Payload Capacity

The vehicle's internal payload support capability includes:

- Size: Up to 34 ft in length
- Volume: Up to ~ 2,000 cu ft internal volume (14 ft length provides ~ 900 cu ft internal volume)
- Capacity: 8 ton dry weight, 18 KW battery power

The vehicle can also accommodate external payloads.



# **XLUUV Summary**

- Weight in Air: 50 tons (45,360 kg)
- Envelope (no payload): 51 ft x 8.5 ft x 8.5 ft (15.5 m x 2.6 m x 2.6 m)
- Envelope (with a 34 ft payload section): 85 ft (25.9 m)
- Maximum Depth: 11,000 ft (3,000 m)
- Maximum Speed: 8.0 kts (14.8 km/hr)
- Minimum Speed: 2.5 kts (4.63 km/hr)
- Optimal Speed: 2.5 3 kts (4.6 5.6 km/hr) •
- Range between recharges: ~150 nm (~280 km) at nominal speed

#### Sonar Payload

Echo Voyager can utilize various types of sonar payload including a Raytheon PROSAS PS60-6000 Synthetic Aperture Sonar to enhance its ocean-bottom mapping capability.

- Swath: 6,234 ft (1,900 m)
- Resolution: 0.3 ft (10cm)
- Altitude: 328 ft (100 m)

Dan Tubbs Program Manager Dan.Tubbs@boeing.com Telephone: (714) 896-5990

Contact:

Paul Siegrist Global Sales & Marketing Lead Paul.W.Siegrist@boeing.com Telephone: (703) 376-9303

www.boeing.com Copyright © 2017 The Boeing Company 311079

Very Long Endurance/Range

Months of operation